

RIG DOG™ IMPACT GLOVES



RIG DOG™ MPCT1000HD

Impact Gloves

Last Updated – (January 2014)

PRODUCT DESCRIPTION

PART #	SIZES	CASE PACK
MPCT1000HD/7S	Small	12 per bag/ 144 per case
MPCT1000HD/8M	Medium	12 per bag/ 144 per case
MPCT1000HD/9L	Large	12 per bag/ 144 per case
MPCT1000HD/10XL	XLarge	12 per bag/ 144 per case
MPCT1000HD/11XXL	XXLarge	12 per bag/ 144 per case

GLOVE COMPOSITION

Shell Material:	Polyester back, synthetic leather palm, fleece liner	Material Color:	Hi-viz yellow back, black palm
Coating Material:	Silicone	Coating Color:	Gray
Other:	Hook and loop wrist closure, reflective piping	Coating Pattern:	“Safety-Grip” dot palm
Country of Origin	China		

PRODUCT FEATURES

- Molded PVC (Polyvinyl Chloride) material provides excellent metacarpal protection from crush and impact on knuckles and fingers
- Thermal fleece liner provides insulation for cold weather applications
- PVC is also placed on key scrape-hazard areas for added protection
- Hi-Viz Spandex fabric stretches easily for flexing to help reduce hand fatigue; bright yellow color allows for visual identification in low-light environments
- Silver, reflective piping enhances low-light visual awareness
- Hook and loop tab closure allows wearer to tighten or loosen cuff for a more comfortable and secure fit
- Silicone Safety-Grip pattern gives wearer a sure grip in oily and wet environments
- Cut and sewn synthetic leather glove is stylish, with reinforced thumb-crotch and no palm seams, providing greater wearer comfort

INDUSTRIES / APPLICATIONS:

- **Oil and Gas**

Also

- Mining
- Construction
- Maintenance
- Fabrication
- Materials Handling

HAND PROTECTION - Technical Data Sheet

CERTIFICATIONS / STANDARDS

OSHA Standard - 29 CFR 1915.157 The employer shall ensure that each affected employee uses appropriate hand protection and other protective clothing where there is exposure to hazards such as skin absorption of harmful substances, severe cuts or lacerations, severe abrasions, punctures, chemical burns, thermal burns, harmful temperature extremes, and sharp objects.

	TEST METHOD	LEVEL	TEST RESULT
CE Certified EN420, EN388 EN388  3111	EN 388		
	Abrasion	3	≥ 2,000 cycles
	Cut	1	≥ 1,2
	Tear	1	≥ 10 newtons
	Puncture	1	≥ 20 newtons
ANSI/ISEA 105	ASTM D3389-05 Abrasion	NA	
	ASTM F1790-97 Cut	NA	

LAUNDERING / STORAGE

Product withstands commercial laundry-room detergents (up to pH 14) and warm water temperatures up to 120°F (49°C). Lower heat settings (up to 180°F) are suggested for drying as extreme heat may cause shrinking and degradation of fiber.

Indefinite shelf life when stored in original packaging in a cool dry place away from light. Recommended temperature range: 50°F to 86°F (10°C to 30°C).



WARNINGS

- Extreme caution should be used around moving machinery.
- Laundering gloves that have been in contact with toxic or corrosive chemicals may result in a chemical reaction, including fumes that could cause personal injury, serious illness or death.

LIMITED WARRANTY

Honeywell Safety products are covered by and subject to the terms of the Honeywell Safety Products Limited Warranty that is printed in our published price list. The Honeywell Safety Products Limited Warranty is the only written warranty of any force and effect, and all other written warranties are disclaimed in their entirety. In no event shall Honeywell Safety Products or any of its authorized dealers be liable for any damages in excess of the purchase price of the relevant product. This limitation applies to damages of any kind, including but not limited to direct or indirect damages or other special, incidental exemplary or consequential damages, whether arising out of the use or inability to use the product, even if we or any of our authorized dealers has been advised of the possibility of the damages or any claim by any other party.

Honeywell Safety Products
900 Douglas Pike
Smithfield, RI 02917
Tel: 800.430.5490

www.honeywellsafety.com